



Applause III

Applause III 02803 NIGHT LIGHT 28531

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Type of product	-	Textile Flooring
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm2)
Smoke Density	ASTM E662	< 450
Commercial warranty	-	Lifetime Limited
Total thickness	ASTM F386	0.290 " (7.39 mm)
Installation method	-	Peel & Stick
Pattern	-	Applause III 02803
Surface treatment	ASTM F410	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern type	-	Texture
Format Type	-	Roll
Pile thickness	ASTM D5848	0.085 " (2.21 mm)
Dye Method	-	Solution Dyed / Yarn Dyed
Secondary backing	-	Powerbond Cushion RS
Primary backing	-	Synthetic Non-Woven
Pattern scale	-	Medium
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Colorfastness to Light	AATCC 16E	> 4 after 60 hours

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	8.50 %
CRI Green Label Plus Certification	-	GLP9744
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Third Party Certification NSF-140	-	Gold